

NVRBCD-8

BCD, Intel® Core™ Processors (Kabylake-S), Cyber Appliance 1U Rackmount Appliance

PRODUCT OVERVIEW

NVRBCD-8 is a surveillance appliance with compact design, integrated a scalable managed switch with PoE+ support, powered by Intel® 7th Gen Core™ I5 CPU and provides up to 4x3.5" swappable HDD tray for sufficient storage. Featuring PoE management software and TPM 2.0 functionality, NVRBCD-8 allows users to build a secured NVR (Network Video Recorder) application at the edge fast and easily.

All appliances are built in-house in BCD's secure facilities. BCD's operations have been assessed by DQS Inc, who certified that we meet the ISO 9001:2015 standard of maintaining a Quality Management System.





KEY FEATURES



DDR4-2400 8GB non-ECC memory, max. 32GB



Intel® 7th Gen Core™ i5-7500 processors



Onboard 8 PoE LAN ports



Four swappable HDD tray



Internal power supply 12V20A /53V5.28A for PoE



RAID Options: 0, 1, 5, 10



Cyber Hardened Video Appliance



20 Harmonize RMM Licenses





NVRBCD-8

BCD, Intel® Core™ Processors (Kabylake-S), Cyber Hardened 1U Rackmount Appliance

SPECIFICATIONS

Main Board

NVRBCD-8 Intel® 7th Gen Core™ i5-7500 processors On board TPM 2.0

Main Memory

(1) \times 8GB DDR4-2400 non-ECC memory, max. 32GB

LAN Features

 $8\times10/100M$ Ethernet ports support PoE+ (max. 30W/port) Support 10/100/1000M ingress between CPU and switch

I/O Interface-Front

Power status/HDD status/LAN status LEDs 1 x USB 3.0 port 4 x 3.5" swappable HDD tray

I/O Interface-Rear

1 x HDMI port

1 x DP port

1 x Power button switch

2 x USB 3.0 ports

1 x RJ45 Management port

1 x RJ45 (10/100/1000M)

1 x SFP (1000M)

8 x 10/100M 802.3at PoE port, max. 30W/port

os

Windows 10 IoT, can be upgraded to Windows Server 2019 or Server 2022

Storage

 $1\times$ SATA M.2 2242/2280 Key M slot, 256GB $4\times3.5^{\circ}$ HDD swappable bay support Software RAID 0.1,5,10

Power Input

Internal power supply 12V20A /53V5.28A for PoE

Dimensions

Chassis dimension: $486 \text{mm} \times 483 \text{mm} \times 44 \text{mm}$ Carton dimension: $775 \text{mm} \times 576 \text{mm} \times 221 \text{mm}$

Weight

Without packing: 14 kg With packing: 17.5 kg

Environment

Operating temperature: 0° C \sim 40° C Storage temperature: -40° C \sim 80° C Relative Humidity: 10% \sim 90% non-condensing

Certifications

CE FCC Class A UL

ORDERING INFORMATION

Barebone

NVRBCD-8 (P/N: TBC)

Supports Intel® 7th Gen Core™ i5-7500 processors, 2 DDR4 memory slots, 8 10/100 PoE LAN ports, M.2 socket, USB ports, HDMI/DP port, 4 swappable 3.5" HDD bays



FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.847.205.1922
TECH SUPPORT: support@bcdinc.com | +1.844.462.2384