

BCD226X-PVS

BCD Professional 2U 26-Bay Rackmount Video Recording Server

MAXIMUM STORAGE DENSITY VIDEO SERVER BUILT FOR PROFESSIONAL PROJECTS









Benefit from next-generation video data archiving and processing with the BCD226X-PVS 2U, 26-Bay rackmount server. With up to 520TB of raw storage, this video server will be a long-term storage solution for the most demanding of projects.

Powered by (2) of the latest Intel® Xeon® Silver Scalable processors, the BCD226X-PVS ensures performance. Memory bandwidth is readily available with (16) DIMM slots for up to 512GB of RDIMM memory, ensuring system resources are always available for high-intensity applications.

System reliability is at the forefront, with (2) 1100W redundant, hot swappable power supplies, as well as RAID 0/1/5/6/10 storage options to help preserve data integrity and provide maximum performance, while a five-year, on-site, next business day, Keep Your Hard Drive warranty ensures peace of mind.



KEY FEATURES

-  Up to 520TB of Raw Storage
-  Intel® Xeon® Silver 4216 Scalable Processors
-  Windows Server 2019
-  iDRAC Express
-  SSD & SATA Drives
-  Redundant Power
-  RAID Options 0, 1, 5, 6, 10
-  5-Year Keep Your Hard Drive Warranty

harmonize Bridge
POWERED BY TIGER TECHNOLOGY
Inside

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993
TECH SUPPORT: support@bcdinc.com

BCD226X-PVS R2.0 Copyright © 2022, BCD. All rights reserved. This document is provided for information purposes only.

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCD226X-PVS

BCD Professional 2U 26-Bay Rackmount Video Recording Server

SYSTEM

Operating System

Windows Server 2019

Memory

Standard Configuration: 32GB (4x 8GB)
Maximum Configuration: Up to 512GB RDIMM,
1TB LRDIMM (16x DDR4 DIMM Slots)

Processor(s)

(2) Intel® Xeon® Silver 4216 Scalable
Processors (16 Cores, 32 Threads, 3.20GHz)

Processor Passmark

Dual Intel® Xeon® Silver 4216: 22,272

Networking

(2) 1GbE RJ45 Ports, (2) 10GbE SFP+ ports

Expansion Slots

(2) PCIe x8 low-profile slots

USB(s)

Rear (2) USB 3.0
Front (1) USB 3.0 & (1) Micro USB 3.0
Internal (1) USB 3.0

Video Outputs

(1) VGA

Remote Management

iDRAC Express

MECHANICAL

Form Factor

2U Rackmount

Power Supply(s)

(2) 1100W (100-240VAC) 80 Plus Platinum

Operating Temperature

(Min) 50°F - (Max) 86° F
(Min) 10°C - (Max) 30° C

Operating Humidity

10 ~ 80% (non-condensing)

Heat Dissipation

3001 Max BTU/hr

Dimensions (WxDxH)

17.63" (448mm) x 33.26" (844.8mm) x 3.41" (86.8mm)

Max. Weight

88.18 lbs. (40 kg)

Warranty

5-Year, On-site, Next Business Day, Keep Your
Hard Drive Warranty

STORAGE

Hard Drive Bays

(26) 3.5" Hot Swappable Bays,
(2) M.2 SSD Slots

Hard Drives Supported

PCIe NVMe & SATA

RAID

RAID 0, 1, 5, 6, 10

RAID Controller

PERC H740P (8GB NV Cache)

Maximum Storage

Up to 520TB of Raw Storage