

BCD226X-PVS

BCD Professional Cyber Hardened 2U 26-Bay Rackmount Video Recording Server

MAXIMUM STORAGE DENSITY VIDEO SERVER BUILT FOR PROFESSIONAL PROJECTS

Benefit from next-generation video data archiving and processing with the BCD226X-PVS 2U, 26-Bay rackmount server. With up to 520TB of raw storage, this video server will be a long-term storage solution for the most demanding of projects.

Powered by (2) of the latest Intel® Xeon® Silver Scalable processors, the BCD226X-PVS ensures performance. Memory bandwidth is readily available with (16) DIMM slots for up to 512GB of RDIMM memory, ensuring system resources are always available for high-intensity applications.

System reliability is at the forefront, with (2) 1100W redundant, hot swappable power supplies, as well as RAID 0/1/5/6/10 storage options to help preserve data integrity and provide maximum performance, while a five-year, on-site, next business day, Keep Your Hard Drive warranty ensures peace of mind.

All appliances are built in-house in BCD's secure facilities. BCD's operations have been assessed by DQS Inc, who certified that we meet the ISO 9001:2015 standard of maintaining a Quality Management System.



FOR MORE INFORMATION: <u>bcdvideo.com</u> | <u>sales@bcdinc.com</u> | +1.888.305.4993 TECH SUPPORT: <u>support@bcdinc.com</u>

BCD226X-PVS R2.0 Copyright © 2023, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

KEY FEATURES





BCD226X-PVS

BCD Professional Cyber Hardened 2U 26-Bay Rackmount Video Recording Server

SYSTEM

Operating System Windows Server 2019

Memory

Standard Configuration: 32GB (4x 8GB) Maximum Configuration: Up to 512GB RDIMM, 1TB LRDIMM (16x DDR4 DIMM Slots)

Processor(s) (2) Intel® Xeon® Silver 4216 Scalable Processors (16 Cores, 32 Threads, 3.20GHz)

Processor Passmark Dual Intel® Xeon® Silver 4216: 22,272

Networking (2) 1GbE RJ45 Ports, (2) 10GbE SFP+ ports

Expansion Slots (2) PCIe x8 low-profile slots

USB(s)

Rear (2) USB 3.0 Front (1) USB 3.0 & (1) Micro USB 3.0 Internal (1) USB 3.0

Video Outputs (1) VGA

Remote Management iDRAC Express

MECHANICAL

Form Factor 2U Rackmount

Power Supply(s) (2) 1100W (100-240VAC) 80 Plus Platinum

Operating Temperature (Min) 50°F - (Max) 86° F (Min) 10°C - (Max) 30° C

Operating Humidity 10 ~ 80% (non-condensing)

Heat Dissipation 3001 Max BTU/hr

Dimensions (WxDxH) 17.63" (448mm) x 33.26" (844.8mm) x 3.41" (86.8mm)

Max. Weight 88.18 lbs. (40 kg)

Warranty 5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty

STORAGE

Hard Drive Bays (26) 3.5" Hot Swappable Bays, (2) M.2 SSD Slots

Hard Drives Supported PCIe NVMe & SATA

RAID RAID 0, 1, 5 6, 10

RAID Controller PERC H740P (8GB NV Cache)

Maximum Storage Up to 520TB of Raw Storage

FOR MORE INFORMATION: <u>bcdvideo.com</u> | <u>sales@bcdinc.com</u> | +1.888.305.4993 TECH SUPPORT: <u>support@bcdinc.com</u>

BCD226X-PVS R2.0 Copyright © 2023, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel Iogo, the Intel Inside Iogo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.