

# BCD214-EVS

BCD Enterprise 2U 14-Bay Cyber-hardened Rackmount Video Recording Server

## ENTERPRISE, HIGH PERFORMANCE AND VIDEO PROCESSING

Benefit from scalable storage performance and dataset processing with the BCD214-EVS server. This 2U, 2-socket platform brings you scalability and performance to adapt to a variety of video surveillance applications. Up to 280TB of raw storage is provided by (14) SAS drives. Paired with the latest Intel<sup>®</sup> Xeon<sup>®</sup> Scalable processor, this provides high-density storage with the throughput for the most demanding applications.

Ease of operation is provided with dual OS SSDs for accelerated boot and application load times. Remote management, provided by iDRAC, allows for constant system status and critical resource monitoring. RAID 5/6 storage options, in addition to redundant 1100W power supplies, provide system high availability while a five-year, on-site, next business day, Keep Your Hard Drive warranty guarantees peace of mind.

All appliances are built in-house in BCD's secure facilities. BCD's operations have been assessed by DQS Inc, who certified that we meet the ISO 9001:2015 standard of maintaining a Quality Management System.





#### FOR MORE INFORMATION: <u>bcdvideo.com</u> | <u>sales@bcdinc.com</u> | +1.888.305.4993 TECH SUPPORT: <u>support@bcdinc.com</u>

BCD214-EVS R2.0 Copyright © 2022, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

## **KEY FEATURES**





## BCD214-EVS

BCD Enterprise 2U 14-Bay Cyber-hardened Rackmount Video Recording Server

### SYSTEM

**Operating System** Windows Server 2019

#### Memory

Single Processor: 16GB (2x 8GB) Dual Processor: 32GB (4x 8GB) Maximum Configuration: Up to 768GB RDIMM, 1.5TB LRDIMM (Up to 24x DDR4 DIMM Slots)

#### Processor(s)

Up to (2) Intel® Xeon® Silver 4210 Scalable Processors (10 Cores, 20 Threads, 3.20GHz)

### Processor Passmark

Intel® Xeon® Silver 4210: 15,794 Dual Intel® Xeon® Silver 4210: 21,000

#### Networking

Single Processor: (2) 1GbE RJ45 Ports, (2) 10GbE SFP+ ports Dual Processor: (4) 1GbE RJ45 Ports, (2) 10GbE SFP+ ports

Optional NIC: (2) 1GbE RJ45 (2) 10GbE SFP+

#### **Expansion Slots**

Single Processor: (2) PCle x16 Fullheight slots (in default configuration) Dual Processor Models: (2) PCle x16 Full-height slots (in default configuration)

#### USB(s)

Front: 2x USB 2.0 & 1x iDRAC Micro- AB port Rear: 2x USB 3.0 ports, Internal = 1 x USB 3.0 port

Video Outputs (1) VGA Port Front & (1) VGA Port Rear

#### Remote Management

iDRAC Express

#### FOR MORE INFORMATION: <u>bcdvideo.com</u> | <u>sales@bcdinc.com</u> | +1.888.305.4993 TECH SUPPORT: <u>support@bcdinc.com</u>

BCD214-EVS R2.0 Copyright © 2022, BCD. All rights reserved. This document is provided for information purposes only.

## MECHANICAL

Form Factor 2U Rackmount

Power Supply(s) (2) 1100W (100-240VAC) 80 Plus Platinum

**Operating Temperature** (Min) 50°F - (Max) 95° F (Min) 10°C - (Max) 35° C

**Operating Humidity** 10 to 80% (non-condensing)

Heat Dissipation 3001 Max BTU/hr

Dimensions (WxDxH) 17.08" (434mm) × 29.875" (758.8mm) × 3.4" (86.8mm)

#### Max. Weight 72.91 lbs (33.1 kg)

Warranty 5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty

## STORAGE

Hard Drive Bays (14) 3.5" Hot Swappable Bays & (2) M.2 SSD Slots

Hard Drives Supported PCIe NVMe & SAS

**Raid** Raid 0, 1, 5 6 & 10

RAID Controller PERC H740P (8GB NV Cache)

Maximum Storage Up to 280TB