



BCD218-EVS

BCD Enterprise Video Appliance 2U 18-Bay Rackmount Video Recording Server

ENTERPRISE, SCALABLE PERFORMANCE FOR VIDEO PROCESSING AND ARCHIVING

Provide scalable storage performance and video data processing with the BCD218-EVS server. This 2U, 2-socket platform brings you scalability and performance to adapt to a variety of the most demanding and process-intensive video surveillance applications.

Up to 360TB of raw storage allows for long-term video storage and archiving, while up to (2) Intel® Xeon® Silver Scalable processors provide unrivaled throughput and computing potential. (24) DDR4 DIMM slots allow for maximum memory bandwidth utilization with support for six-channel memory architecture.

Dual M.2 SSDs for the operating system and application accelerated load times. System reliability and high availability is guaranteed with redundant 1100W power supplies and RAID 0/1/5/6/10 storage options, while a five-year, on-site, next business day, Keep Your Hard Drive warranty ensures peace of mind.

All appliances are built in-house in BCD's secure facilities. BCD's operations have been assessed by DQS Inc, who certified that we meet the ISO 9001:2015 standard of maintaining a Quality Management System.





KEY FEATURES



Cyber Hardened Video Appliance



Up to 360TB of Raw Storage



Intel® Xeon® Silver Scalable Processors



Windows Server 2019



iDRAC Express With Lifecycle Controller



SSD & SAS Drives



Redundant Power



RAID Options 0, 1, 5, 6, 10



5-Year Keep Your Hard Drive Warranty



20 Harmonize RMM Licenses



FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993





BCD218-EVS

BCD Enterprise Cyber Hardened 2U 18-Bay Rackmount Video Recording Server

SYSTEM

Operating System

Windows Server 2019

Memory

Single Processor: 16GB (2x 8GB)
Dual Processor: 32GB (4x 8GB)
Maximum Configuration: Up to 768GB
RDIMM, 1.5TB LRDIMM, 192GB NVDIMM
(24x DDR4 DIMM Slots)

Processor(s)

Up to (2) Intel® Xeon® Silver Scalable Processors (16 Cores, 32 Threads, 3.20GHz)

Processor Passmark

Intel® Xeon® Silver 4216: 18,561 Dual Intel® Xeon® Silver 4216: 22,272

Networking

Single Processor: (4) 1GbE RJ45 Ports Dual Processor: (4) 1GbE RJ45 Ports, (2) 10GbE SFP+ ports

Expansion Slots

(2) Full-height PCle x8,(1) Low-profile x8 slots available

USB(s)

Rear (2) USB 3.0 Front (2) USB 2.0, Internal (1) USB 3.0

Video Outputs

(1) VGA front & back

Remote Management

iDRAC Express

MECHANICAL

Form Factor

2U Rackmount

Power Supply(s)

(2) 1100W (100-240VAC) 80 Plus Platinum

Operating Temperature

(Min) 50°F - (Max) 95° F (Min) 10°C - (Max) 35° C

Operating Humidity

10 ~ 80% (non-condensing)

Heat Dissipation

3001 Max BTU/hr

Dimensions (WxDxH)

17.09" (434mm) x 26.72" (678.8mm) x 3.4" (86.8mm)

Max. Weight

73 lbs. (33.1kg)

Warranty

5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty

STORAGE

Hard Drive Bays

(18) 3.5" Hot Swappable Bays & (2) M.2 SSD Slots

Hard Drives Supported

PCIe NVMe & SAS

RAID

RAID 0, 1, 5 6, 10

RAID Controller

PERC H740P (8GB NV Cache)

Maximum Storage

Up to 360TB



FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com