

BCD218-EVS

BCD Enterprise 2U 18-Bay Rackmount Video Recording Server

ENTERPRISE, SCALABLE PERFORMANCE FOR VIDEO PROCESSING AND ARCHIVING









Provide scalable storage performance and video data processing with the BCD218-EVS server. This 2U, 2-socket platform brings you scalability and performance to adapt to a variety of the most demanding and process-intensive video surveillance applications.

Up to 360TB of raw storage allows for long-term video storage and archiving, while up to (2) Intel® Xeon® Silver Scalable processors provide unrivaled throughput and computing potential. (24) DDR4 DIMM slots allow for maximum memory bandwidth utilization with support for six-channel memory architecture.

Dual M.2 SSDs for the operating system and application accelerated load times. System reliability and high availability is guaranteed with redundant 1100W power supplies and RAID 0/1/5/6/10 storage options, while a five-year, on-site, next business day, Keep Your Hard Drive warranty ensures peace of mind.



KEY FEATURES

-  Up to 360TB of Raw Storage
-  Intel® Xeon® Silver Scalable Processors
-  Windows Server 2019
-  iDRAC Express With Lifecycle Controller
-  SSD & SAS Drives
-  Redundant Power
-  RAID Options 0, 1, 5, 6, 10
-  5-Year Keep Your Hard Drive Warranty

harmonize Bridge
POWERED BY TIGER TECHNOLOGY
Inside

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

BCD218-EVS R2.0 Copyright © 2022, BCD. All rights reserved. This document is provided for information purposes only.

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCD218-EVS

BCD Enterprise 2U 18-Bay Rackmount Video Recording Server

SYSTEM

Operating System

Windows Server 2019

Memory

Single Processor: 16GB (2x 8GB)
Dual Processor: 32GB (4x 8GB)
Maximum Configuration: Up to 768GB
RDIMM, 1.5TB LRDIMM, 192GB NVDIMM
(24x DDR4 DIMM Slots)

Processor(s)

Up to (2) Intel® Xeon® Silver Scalable Processors (16 Cores, 32 Threads, 3.20GHz)

Processor Passmark

Intel® Xeon® Silver 4216: 18,561
Dual Intel® Xeon® Silver 4216: 22,272

Networking

Single Processor: (4) 1GbE RJ45 Ports
Dual Processor: (4) 1GbE RJ45 Ports,
(2) 10GbE SFP+ ports

Expansion Slots

(2) Full-height PCIe x8,
(1) Low-profile x8 slots available

USB(s)

Rear (2) USB 3.0
Front (2) USB 2.0,
Internal (1) USB 3.0

Video Outputs

(1) VGA front & back

Remote Management

iDRAC Express

MECHANICAL

Form Factor

2U Rackmount

Power Supply(s)

(2) 1100W (100-240VAC) 80 Plus Platinum

Operating Temperature

(Min) 50°F - (Max) 95° F
(Min) 10°C - (Max) 35° C

Operating Humidity

10 ~ 80% (non-condensing)

Heat Dissipation

3001 Max BTU/hr

Dimensions (WxDxH)

17.09" (434mm) x 26.72" (678.8mm) x 3.4" (86.8mm)

Max. Weight

73 lbs. (33.1kg)

Warranty

5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty

STORAGE

Hard Drive Bays

(18) 3.5" Hot Swappable Bays &
(2) M.2 SSD Slots

Hard Drives Supported

PCIe NVMe & SAS

RAID

RAID 0, 1, 5, 6, 10

RAID Controller

PERC H740P (8GB NV Cache)

Maximum Storage

Up to 360TB

