





BCD784S-SAN-ADA-HE-210

BCD Deepstor® Bundle Certified for Avigilon Control Center

2U RACKMOUNT, ENTRY-LEVEL, **EXPANDABLE VIDEO RECORDING SERVER**

The BCD784S-SAN-ADA-HE-210 bundles BCD's 206 2U rackmount server with the Deepstor 5U 84 Bay SAN, pre-loaded with Avigilon Control Center. Up to 1.68TB of raw video-optimized storage is provided by 24/7 duty cycle SATA drives.

In addition to petabyte-scale storage, this bundle offers a simple and easy-to-deploy SAN system with BCD's exclusive quick-start configuration tool, as well as Harmonize iDRAC for proactive system health monitoring.

Guarantee fast response times and free up system resources with (4) 8GB DDR4 RAM, 48GB controller memory, and (1) NVIDIA T1000.

System stability and peace of mind is provided with redundant, hot swappable power supplies, an operating system running on solid state drives, and a five-year, on-site, next business day, Keep Your Hard Drive warranty.



KEY FEATURES



Up to 1.68PB of Raw Storage, 6.72PB with Expansion



Dual Intel® Xeon® Silver 4210 Scalable Processors



NVIDIA® T1000 Graphics Card



Throughput: 1100 Mb/s



Windows Server 2022



iDRAC Enterprise



SSD & Enterprise SAS Drives



Redundant Power



RAID Options: 0, 1, 5, 6, 10



5-Year, On-Site, Next Business Day, **Keep Your Hard Drive Warranty**



20 Harmonize RMM Licenses



FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993 TECH SUPPORT: support@bcdinc.com







BCD784S-SAN-ADA-HE-210

BCD Deepstor® Bundle Certified for Avigilon Control Center

SYSTEM

Operating System

Windows Server 2022

Memory

32GB (4x 8GB)

Processor(s)

(2) Intel® Xeon® Silver 4210 Scalable Processors (10 Cores, 20 Threads, 3.20GHz)

Processor Passmark

Dual: Intel® Xeon® Silver 4210: 23,610

Networking

(2) 1GbE RJ45 (2) 10GbE SFP+

USB(s)

Front: 2 x USB 2.0 & 1 x iDRAC Micro-AB port Internal = 1 x USB 3.0 port Rear: 2 x USB 3.0 ports

Connectivity Fibre Channel

2U: Up to 32GB Fibre Channel 5U: Up to 32GB Fibre Channel, Up to 25Gb iSCSI

Video Outputs

(1) VGA Port Front, (1) VGA Port Rear

Remote Management

iDRAC Enterprise

GPU Acceleration

(1) NVIDIA T1000

MECHANICAL

Form Factor

2U Rackmount + 5U Rackmount

Power Supply(s)

2U: (2) 1100W (100-240VAC) 80 Plus Platinum 5U: (2) 2200W (200-240VAC)

Operating Temperature

2U and 5U: (Min) 50°F - (Max) 95° F (Min) 10°C - (Max) 35° C

Operating Humidity

2U: 10 to 80% (non-condensing) 5U: -12°C DP and 10% RH to 21°C DP and 80%RH, max DP 21°C / 5% to 100% noncondensing

Heat Dissipation

2U: 3001 Max BTU/hr 5U: 7507 Max BTU/hr

Dimensions (WxDxH)

2U: 17.08" (434mm) x 28.17" (715.5mm) x 3.4" (86.8mm) 5U: 19" (483mm) x 36.75" (933mm) x 8.65" (220mm)

Max. Weight

2U: 63.05 lbs. (28.6 kg) 5U: 298 lbs. (135 kg)

Warranty

5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty



STORAGE

Hard Drive Bays

(84) 3.5" Hot Swappable Bays (5U) 512GB M.2 SSD used for the OS

PAID

RAID levels 0, 1, 5 6, 10 and ADAPT

RAID Controller

PERC H740P RAID Controller (8G NV Cache)

Read IOPS

725K

Read/Write Throughput

12 GB/s / 10GB/s

Volumes per System

1024

Maximum Storage

Up to 1.68PB of Raw Storage, 1.312PB Usable Up to 6.72PB with expansion

Regulatory

UL 60950-1 (United States), CAN/CSA-C22.2 No.60950-1-07 (Canada), EN 60950-1

(European Union), IEC 60950-1 (International), CCC (China PRC - CCC Power Supplies), BIS

(India - BIS Power Supplies) FCC CFR 47 Part 15 Subpart B Class A (United States), ICES/NMB-003 Class A (Canada), EN 55022/EN 55032:2012 Class A (EU), AS/NZS CISPR 22/ CISPR 32 Class A

(Australia/New Zealand), VCCI Class A (Japan), KN 22/KN 32 Class A (S. Korea), CNS 13438 Class A (Taiwan) EN 61000-3-2 (EU) EN

61000-3-3 (EU) EN 55024 (EU), KN 24/ KN 35 (S. Korea) The RoHS Directive (2011/65/

EU), The WEEE Directive (2012/19/EU), The REACH Directive (EC/1907/2006), The Batteries Directive

(2006/66/EC) Australia/New Zealand (RCM), Canada (cUL/ ICES/NMB-003 Class A), China

(CCC - PSU only), European Union (CE), Japan (VCCI), South Korea (MSIP), Taiwan (BSMI),

United States (FCC/UL)

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993 TECH SUPPORT: support@bcdinc.com