D&LLTechnologies BCD

MON-24-FHD

24 Inch Client Viewing Monitor with Full HD

GENERAL

Display Type LED-backlit LCD Monitor / TFT Active Matrix

Diagonal Size 23.8"

Panel Type VA

Aspect Ratio 16:9

Native Resolution Full HD (1080p) 1920 x 1080 at 60 Hz

Brightness 250 cd/m²

Contrast Ratio 3000:1 / 3000:1 (dynamic)

Color Gamut 72% NTSC (CIE 1931), 83% NTSC (CIE 1976)

Response Time 5 ms (gray-to-gray fast) 8 ms (gray-to-gray normal)

Backlight Technology LED Backlight

AUDIO

Speakers Stereo

CONNECTIVITY

Connectivity Interfaces (1) DisplayPort 1.2 (1) VGA (1) HDMI

ENVIRONMENTAL

Operating Temperature 32 °F - 104°F (0°C - 40°C)

Humidity Range Operating 10 - 80% (non-condensing)

Environmental Standards EPEAT Compliant: EPEAT Gold ENERGY STAR Certified: Yes

SUPPORT

Warranty 5Year 24/7 ProSupport and Advanced Exchange Warranty

MECHANICAL

Mechanical Display Position Adjustments Height, swivel, tilt - Tilt Angle: -5/+21 Swivel Angle: 346 Height Adjustment: 5.3 in VESA Mounting Interface: 100 x 100 mm

Cables Included

Power Cable
HDMI cable
DisplayPort cable
VGA cable

Power

Input Voltage: AC 100-240 V (50/60 Hz) Power Consumption (On mode): 16 W Power Consumption (Typical): 28W Power Consumption Stand by: 0.3 W Power Consumption Sleep: 0.3W Power Consumption (Off Mode): 0.3 W On / Off Switch: Yes

Dimensions (W x D x H) and Weight

With stand (lowest position): width: 21.2 in - depth: 8.2 in - height: 14.9 in - weight: 10 lbs With stand (highest position): width: 21.2 in - depth: 8.2 in - height: 20.2 in - weight: 10 lbs Without stand: width: 21.2 in - depth: 1.9 in - height: 12.8 in - weight: 6.2 lbs Shipping Weight: 13.14 lbs



FOR MORE INFORMATION: <u>bcdvideo.com</u> | <u>sales@bcdinc.com</u> | +1.888.305.4993 TECH SUPPORT: <u>support@bcdinc.com</u>

MON-43-4K R1.0 Copyright © 2023, BCD. All rights reserved. This document is provided for information purposes only. The Dell logo is a registered trademark of Dell Technologies or its subsidiaries in the U.S. and/or other countries.