

MON-43-4K

43 Inch Client Viewing Monitor with 4K Resolution

GENERAL

Display Type

Active Matrix - TFT LCD

Diagonal Size

42.51"

Built-in Devices

USB 3.2 Gen 2 USB-C Hub

USB Power Delivery

90 Watt

Panel Type

IPS

Aspect Ratio

16:9

Native Resolution

4K (3840 \times 2160) at 60 Hz

Brightness

 350 cd/m^2

Color Gamut

95% sRGB

Response Time

5 ms (gray-to-gray fast) 8 ms (gray-to-gray normal)

Backlight Technology

LED Backlight

AUDIO

Speakers

Output Power / Channel - (2) 8W

KVM

Keyboard/Mouse Interface

USB

CONNECTIVITY

Connectivity Interfaces

(2) DP 1.4 - 2 x HDMI 2.1 (TMDS)

(1) USB-C (DP.14 HB3 (2lane) / HBR2 (4 Lane), Power Delivery up to 90W, 2/4 lane switching), USB 3.2 Gen 2 10Gbps) upstream

(3) USB-C (USB 3.2 Gen2,10Gbps KVM) Upstream port, Data Only

(3) super speed USB-A (USB 3.2 Gen 2 10Gbps) downstream ports

(1) super speed USB A (USB3.2 Gen 2 10Gbps) with B.C 1.2

(1) USB C (USB3.2 Gen 2,10 Gbps, Upto 15W charging) downstream Quick access port

(1) Analog 2.0 audio line out (3.5mm jack)

(1) RJ45 Port (PXE boot, MAC address pass thru, WoL, 1Gbps) Quick Access port

ENVIRONMENTAL

Operating Temperature

32 °F - 104°F (0°C - 40°C)

Humidity Range Operating

10 - 80% (non-condensing)

Environmental Standards

EPEAT Compliant: EPEAT Gold ENERGY STAR Certified: Yes

SUPPORT

Warranty

5Year 24/7 ProSupport and Advanced Exchange Warranty

MECHANICAL

Mechanical Display Position Adjustments

Height, swivel, tilt - Tilt Angle: -5/+10 - Swivel Angle: -20° to 20° $\,$

Height Adjustment: 2.4 in

VESA Mounting Interface: 100×100 mm, 200×200

mm

Cables Included

(1) Power Cable

(1) DisplayPort 1.80 m cable (DisplayPort to DisplayPort)

(1) USB-A to USB-C Gen 2 Cable 1.0m (A to C)

(1) USB-C Gen 2 PD 3.0 1.0m cable

(1) HDMI 1.80m Cable

Power

Input Voltage: AC 100-240 V (50/60 Hz)
Power Consumption (On mode) 52.1 W
Power Consumption (Typical): 250 W
Power Consumption (Stand By): 0.3W
Power Consumption (Off Mode): 0.3W
On / Off Switch: Yes

Dimensions (W x D x H) and Weight

With stand (lowest position) - 38.1" \times 10.1" \times 23.4" Weight: 40.9 lbs

With stand (highest position) - 38.1" \times 10.1" \times 25.8"

Weight: 40.9 lbs

Without stand - 38.1" \times 2.5" \times 22.1"

Weight: 29 lbs

Shipping Weight: 55.62 lbs

