

BCD-HES02-I5-8RJ / BCD-HES02-I7-8RJ

BCDVideo 2-Bay Small Form Factor Harsh Environment Server

8 PORT POE HARSH ENVIRONMENT SERVER










The BCD-HES02-I5-8RJ and BCD-HES02-I7-8RJ support 8-port Gigabit PoE and able to work under harsh temperatures.

Its eight Gigabit PoE ports allow multiple cabling to cameras and any PoE power device. Powered by an Intel® Core™ i5 or i7 processor, this unit also has two front-accessible SIM slots and four SMA-type antenna connectors.

For storage, this high performance fanless server has two drive bays with a height of up to 15 mm and one optional mSATA for RAID 0 and 1. Moreover, the embedded device supports two non-ECC 260-pin DDR4 SO-DIMM slots for up to 32GB of system memory.



KEY FEATURES

-  Up to 8TB Storage
-  Intel® Core™ 7th Generation Processor
-  Windows 10 Pro
-  Wide Temp SSDs
-  32GB DDR4 RAM
-  Supports Cell/GPS/Wi-Fi Modules
-  -40°C to +70°C (-40°F to +158°F)
-  (8) RJ45 PoE Ports
-  3-Year Advanced Replacement Warranty

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

BCD-HES02-8RJ R1.0 Copyright © 2022, BCD. All rights reserved. This document is provided for information purposes only.

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCD-HES02-I5-8RJ / BCD-HES02-I7-8RJ

BCDVideo 2-Bay Small Form Factor Harsh Environment Server

SYSTEM

Operating System

Windows 10 Pro

Memory

Standard Configuration: 16GB (2x 8GB)
Maximum Configuration: Up to 32GB
(2x DDR4 SO-DIMM Slots)

Processor(s)

(1) Intel® Core™ 7th Generation Processor
(Up to 4 Cores, 8 Threads, 3.80GHz)

Processor Passmark

Intel® Core i5-7500T: 6,950
Intel® Core™ i7-7700T: 9,288

Networking

(8) 1GbE RJ45 PoE Ports
(IEEE 802.3af/802.3at)

Expansion Slots

(2) Full-size PCIe Mini Card Slot,
(1) Half-size PCIe Mini Card Slot
(1) Half-size PCIe Mini Card,
USB Mini Card slot, (2) SIM Slots

I/O Ports

(4) USB 3.0, (2) USB 2.0, (2) RS-232/422/485, (4) SMA Antenna Connectors, (1) 6-in/2-out Isolated DIO

Video Outputs

(1) VGA, (1) HDMI 1.4b, (1) DVI-D

Certifications

CE, FCC Class A, IP40

Manufacturer

BCD

MECHANICAL

Form Factor

Small Form Factor

Power Supply(s)

(1) 24V 120W External (10 - 30VDC) or (1) 230W
(10-30VDC)

Operating Temperature

Chassis Operating Temperature: -40°F to 158°F
[-40°C to +70°C] with Wide Temp peripherals
Standard Temp SSDs: 32°F to 158°F [0°C to +70°C]
Wide Temp SSDs: -40°F to 185°F [-40°C to +85°C]

Operating Humidity

10 ~ 90% (non-condensing)

Heat Dissipation

327 Max BTU/hr

Dimensions (WxDxH)

11.2" x 8.26" x 3.13" (280mm x 210mm x 79.6mm)

Max. Weight

11.24 lb (5.1 kg)

Warranty

3-Year Advanced Replacement

EMC

EN 50155, EN 50121, IEC 62236-3-2 Compliant
CE/FCC: EN 55032 (Class A), EN 55024, FCC
Part 15 B (Class A)

Shock Endurance

IEC 60068-2-27 (with SSD, 50G, half sine, 11ms duration)

Vibration Endurance

IEC 60068-2-64 (with SSD, 3Grms STD,
random 5 to 500 Hz, 1hr/axis)

STORAGE

Hard Drive Bays

(1) 256GB mSATA
(2) 15mm 2.5" Drive Bays

Hard Drives Supported

SATA

RAID

JBOD

Maximum Storage

Up to 8TB (2TB or 4TB Standard
& Wide Temp Drives Available)