

BCD104-EVS


BCDVideo Enterprise 1U 4-Bay Rackmount Video Recording Server

POWERFUL AND VERSATILE ENTERPRISE 1U RACKMOUNT SERVER









Manufactured for enterprise IP video surveillance applications and fully customizable for individual project requirements, the BCD104-EVS enterprise video server provides unrivaled value and performance.

With bi-directional, dual port SAS drives providing up to 64TB of raw storage, the latest Intel® Xeon® E series and Silver processors, and up to 64GB of DDR4 RAM, the BCD104-EVS guarantees the throughput needed for any project.

Redundant, hot swappable power supplies and RAID 5/6 storage options provide high system availability. A pair of M.2 solid state drives for the operating system and applications provide reliability and fast application load times for added performance, while a five-year, on-site, next business day, Keep Your Hard Drive warranty guarantees peace of mind.



KEY FEATURES

-  Up to 64TB of Raw Storage
-  Intel® Xeon® E Series & Silver Processors
-  Windows Server 2019
-  iDRAC Express
-  SSD & SATA Drives
-  Redundant Power
-  RAID Options 0, 1, 5, 6, 10
-  5-Year Keep Your Hard Drive Warranty

harmonize Bridge
POWERED BY TIGER TECHNOLOGY
Inside

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993
TECH SUPPORT: support@bcdinc.com

BCD104-EVS R1.0 Copyright © 2021, BCD. All rights reserved. This document is provided for information purposes only.

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCD104-EVS

BCDVideo Enterprise 1U 4-Bay Rackmount Video Recording Server

SYSTEM

Operating System

Windows Server 2019

Memory

Single CPU: 16GB (2x 8GB)
Dual CPU: 32GB (2x 16GB)
Maximum Configuration: Up to 64GB
(4x DDR4 DIMM Slots)

Processor(s)

Intel® Xeon® E-2236
(6 cores, 12 threads @ 3.40GHz)
Intel® Xeon® Silver 4210
(10 cores, 20 threads @ 3.20GHz)

Processor Passmark

Intel® Xeon® E-2236: 14,333
Intel® Xeon® Silver 4210: 14,507
Dual Intel® Xeon® Silver 4210: 23,437

Networking

Single CPU: (2) 1GbE RJ45 Ports
Dual CPU: (2) 1GbE RJ45 Ports &
(2) 10GbE SFP+ Ports

Expansion Slots

2x PCIe Gen 3.0 slots: (1) x8 slot
low-profile, half-length with x4 slot
width, (1) x16 slot low-profile/full-height,
half-length with x8 bandwidth

USB(s)

Rear (2) USB 3.0, Front (1) USB 2.0

Video Outputs

(1) VGA

Remote Management

iDRAC Express

MECHANICAL

Form Factor

1U Rackmount

Power Supply(s)

Single CPU: 350W (100-240VAC) 80 Plus Platinum
Dual CPU: (2) 550W (100-240VAC) 80 Plus Platinum

Operating Temperature

(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]

Operating Humidity

10 ~ 80% (non-condensing)

Heat Dissipation

Single CPU: 955 Max BTU/hr
Dual CPU: 1500 Max BTU/hr

Dimensions (WxDxH)

Xeon® E-2236: 17.08" (434mm) x 22.58"
(573.6mm) x 1.68" (42.8mm)
Xeon® Silver 4210: 17.08" (434mm) x 28.13"
(714.62mm) x 1.68" (42.8mm)

Max. Weight

Xeon® E-2236: 29.98 lbs. (13.6 kg)
Xeon® Silver 4210: 38.9 lbs (17.6 kg)

Warranty

5-Year, On-site, Next Business Day, Keep Your Hard
Drive Warranty

Manufacturer

BCD

STORAGE

Hard Drive Bays

(4) 3.5" Hot Swappable Bays &
(2) M.2 SSD Slots

Hard Drives Supported

PCIe NVMe & SAS

RAID

OS RAID: 0, 1
Data RAID: 0, 1, 5, 6, 10

RAID Controller

PERC H730P (2GB NV Cache)

Maximum Storage

Up to 64TB