

BCD208-EVS

BCDVideo Enterprise 2U 8-Bay Rackmount Video Recording Server

ENTERPRISE 2U RACKMOUNT, EXPANDABLE VIDEO RECORDING SERVER









The BCD208-EVS enterprise 2U 8-bay video recording server boasts exceptional performance with unrivaled expandability within its chassis. Optimized for performance-demanding video surveillance applications, this video server uses the latest hardware to deliver results.

Support for up to (2) Intel® Xeon® Scalable Silver 4210 processors ensures computing performance, while (16) DDR4 DIMM slots provide up to 512GB RDIMM/1TB LRDIMM of DDR4 ECC RAM for ample memory resources for immense bandwidth applications.

Video storage options are available with up to (8) 3.5" enterprise SAS drives and support of RAID 5/6 for data protection and optimized performance. Dual 1100W platinum-rated power supplies provide proper power resources for all hardware. The BCD208-EVS also comes with a 5-year, on-site, next business day, keep your hard drive warranty.



KEY FEATURES

-  Up to 128TB of Raw Storage
-  Intel® Xeon® Silver 4210 Scalable Processor
-  Windows Server 2019
-  iDRAC Express With Lifecycle Controller
-  SSD & SAS Drives
-  Redundant Power
-  RAID Options: 0, 1, 5, 6, 10
-  5-Year Keep Your Hard Drive Warranty

harmonize Bridge
POWERED BY TIGER TECHNOLOGY
Inside

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993
TECH SUPPORT: support@bcdinc.com

BCD208-EVS R1.0 Copyright © 2021, BCD. All rights reserved. This document is provided for information purposes only.

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCD208-EVS

BCDVideo Enterprise 2U 8-Bay Rackmount Video Recording Server

SYSTEM

Operating System

Windows Server 2019

Memory

Single Processor: 16GB (2x 8GB)
Dual Processor: 32GB (4x 8GB)
Maximum Configuration: Up to 512GB
RDIMM, 1TB LRDIMM (16x DDR4 DIMMs Slots)

Processor(s)

Up to (2) Intel® Xeon® Silver 4210
Scalable Processors
(Up to 10 Cores, 20 Threads, 3.20GHz)

Processor Passmark

Intel® Xeon® Silver 4210: 15,794
Dual Intel® Xeon® Silver 4210: 21,000

Networking

Single Processor: (2) 1GbE RJ45 Ports
Dual Processor: (2) 1GbE RJ45 Ports,
(2) 10GbE SFP+ Ports

Expansion Slot

Single Processor: (1) PCIe x16 full-height
Half Length PCIe slot
Dual Processor: (4) PCIe x16 Half Height
Half Length low-profile slots

USB(s)

Front = 2x USB 2.0 & 1x iDRAC Micro-AB port:
Rear = 2x USB 3.0 ports,
Internal = 1x USB 3.0 port

Video Outputs

(1) VGA Port Front & (1) VGA Port Rear

Remote Management

iDRAC Express

MECHANICAL

Form Factor

2U Rackmount

Power Supply(s)

(2) 1100W (100-240VAC) 80 Plus Platinum

Operating Temperature

(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]

Operating Humidity

10 to 80% (non-condensing)

Heat Dissipation

3001 Max BTU/hr

Dimensions (WxDxH)

17.08" (434mm) x 27.31" (693.67mm) x 3.4" (86.8mm)

Max. Weight

56 lbs (25.4 kg)

Warranty

5-Year, On-site, NBD, Keep Your Hard
Drive Warranty

Manufacturer

BCD

STORAGE

Hard Drive Bays

(8) 3.5" Hot Swappable Bays &
(2) M.2 SSD Slots

Hard Drives Supported

PCIe NVMe & SAS

RAID

RAID levels 0, 1, 5 6, 10

RAID Controller

PERC H740P RAID Controller (8G NV Cache)

Maximum Storage

Up to 128TB