

BCDSF02S-IVS

BCDVideo 2-Bay Small Form Factor In-Vehicle / Harsh Environment Server

8 PORT POE IN-VEHICLE SERVER









The BCDSF02S-IVS supports 8-port Gigabit PoE and able to work under harsh temperatures.

Its eight Gigabit PoE ports allow multiple cabling to cameras and any PoE power device. Powered by Intel® Core™ i5 or i7 processors. It also has two front-accessible SIM slots and four SMA-type antenna connectors.

For storage, this high performance fanless in-vehicle server has two drive bays with a height of up to 15 mm and one optional mSATA for RAID 0 and 1. Moreover, the embedded device supports two non-ECC 260-pin DDR4 SO-DIMM slots for up to 32GB of system memory.



KEY FEATURES

-  Up to 10TB Storage
-  Intel® Core™ 7th Generation Processor
-  Windows 10 Pro
-  SSD & 24/7 Duty Cycle SATA Drives
-  32GB DDR4 RAM
-  Supports Cell/GPS/Wi-Fi Modules
-  -40°C to +50°C (-40°F to +122°F)
-  (8) RJ45 PoE Ports
-  3-Year Advanced Replacement Warranty

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

BCDSF02S-IVS R1.0 Copyright © 2021, BCD. All rights reserved. This document is provided for information purposes only.

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCDSF02S-IVS

BCDVideo 2-Bay Small Form Factor In-Vehicle / Harsh Environment Server

SYSTEM

Operating System

Windows 10 Pro

Memory

Standard Configuration: 16GB (2x 8GB)
Maximum Configuration: Up to 32GB
(2x DDR4 SO-DIMM Slots)

Processor(s)

(1) Intel® Core™ 7th Generation Processor
(Up to 4 Cores, 8 Threads, 3.80GHz)

Processor Passmark

Intel® Core™ i5-7500T: 6,950
Intel® Core™ i7-7700T: 9,288

Networking

(8) 1GbE RJ45 PoE Ports
(IEEE 802.3af/802.3at)

Expansion Slots

(2) Full-size PCIe Mini Card Slot,
(1) Half-size PCIe Mini Card Slot
(1) Half-size PCIe Mini Card,
USB Mini Card slot, (2) SIM Slots

I/O Ports

(4) USB 3.0, (2) USB 2.0, (2) RS-
232/422/485, (4) SMA Antenna Connectors,
(1) 6-in/2-out Isolated DIO

Video Outputs

(1) VGA, (1) HDMI 1.4b, (1) DVI-D

Certifications

CE, FCC Class A, IP40

Manufacturer

BCD

MECHANICAL

Form Factor

Small Form Factor

Power Supply(s)

(1) 24V 120W External (10 - 30VDC)

Operating Temperature

-40°F - 122° F [-40°C - 50° C]
or -40°F to 158°F [40°C to +70°C]
with Wide Temperature peripherals

Operating Humidity

10 ~ 90% (non-condensing)

Heat Dissipation

327 Max BTU/hr

Dimensions (WxDxH)

11.2" x 8.26" x 3.13" (280mm x 210mm x 79.6mm)

Max. Weight

11.24 lb (5.1 kg)

Warranty

3-Year Advanced Replacement

EMC

EN 50155, EN 50121, IEC 62236-3-2 Compliant
CE/FCC: EN 55032 (Class A), EN 55024,
FCC Part 15 B (Class A)

Shock Endurance

IEC 60068-2-27 (with SSD, 50G, half sine,
11ms duration)

Vibration Endurance

IEC 60068-2-64 (with SSD, 3Grms STD,
random 5 to 500 Hz, 1hr/axis)

STORAGE

Hard Drive Bays

(1) mSATA Slot &
(2) 15mm 2.5" Drive Bays

Hard Drives Supported

SATA

RAID

JBOD

Maximum Storage

Up to 10TB HDD, 1TB SSD