

# BCDSF04S-IVS

## 4-Bay Small Form Factor In-Vehicle / Harsh Environment Server

### 16 PORT POE IN-VEHICLE SERVER










The BCDSF04S-IVS is powered by Intel® Core™ i5-7500T or i7-7700T processors. The integrated 16 PoE ports are RJ-45 connectors for IP cameras.

It provides a full scope of power protection that includes intelligent vehicle power management technology for ACC on/off delay, shutdown delay, and over/under voltage protection. Enhanced by its robust structure and system design, the BCDSF04S-IVS is able to operate under a wide temperature range from -40°F to +158°F and vibration endurance up to 3 Grms.

This in-vehicle server is in compliance with E-Mark and EN 50155 for mobile surveillance applications. With wireless LAN modules, this userfriendly in-vehicle server can real-time transmits the video to the control center. The four built-in swappable SATA hard drives are used for mass storage of video files.



### KEY FEATURES

-  Up to 16TB Storage
-  Intel® Core™ 7th Generation Processor
-  Windows 10 Pro
-  SSD & 24/7 Duty Cycle SATA Drives
-  16GB DDR4 RAM
-  Supports Cell/GPS/Wi-Fi Modules
-  -40°C to +70°C (-40°F to +158°F)
-  EN 50155 Certified
-  3-Year Advanced Replacement Warranty

FOR MORE INFORMATION: [bcdvideo.com](http://bcdvideo.com) | [sales@bcdinc.com](mailto:sales@bcdinc.com) | +1.888.305.4993  
 TECH SUPPORT: [support@bcdinc.com](mailto:support@bcdinc.com)

# BCDSF04S-IVS

## 4-Bay Small Form Factor In-Vehicle / Harsh Environment Server

### SYSTEM

#### Operating System

Windows 10 Pro

#### Memory

Standard Configuration: 16GB (2x 8GB)  
Maximum Configuration: Up to 32GB  
(2x DDR4 SO-DIMM Slots)

#### Processor(s)

(1) Intel® Core™ 7th Generation Processor  
(Up to 4 Cores, 8 Threads, 3.80GHz)

#### Processor Passmark

Intel® Core™ i5-7500T: 6,950  
Intel® Core™ i7-7700T: 9,288

#### Networking

(16) 1GbE RJ45 PoE Ports  
(IEEE 802.3af/802.3at)

#### Expansion Slots

(2) Full-size PCIe Mini Card Slot,  
(2) USB/PCIe External SIM Socket,  
(2) Half-size PCIe Mini Card Slot

#### I/O Ports

(4) USB 3.0, (2) DB-9 or RS-232/422/485, (5) Antenna Openings,  
(1) Terminal Block 6-in/2-out DIO

#### Video Outputs

(1) HDMI, (1) DVI-D, (1) VGA

#### Certifications

CE (Class A), FCC Class A, EN 50155,  
ISO 7637-2 Compliant

#### Manufacturer

BCD

### MECHANICAL

#### Form Factor

Small Form Factor

#### Power Supply(s)

(1) 24V 120W External (10 - 30VDC)

#### Operating Temperature

(Min) -40°F - (Max) 158° F [(Min) -40°C - (Max) 70° C]  
With Wide Temperature Peripherals

#### Operating Humidity

0 ~ 95% (non-condensing)

#### Heat Dissipation

327 Max BTU/hr

#### Dimensions (WxDxH)

11.02" x 8.27" x 3.91" (280mm x 210.5mm x 99.2mm)

#### Max. Weight

12.65 lbs. (5.74 kg)

#### Warranty

3-Year Advanced Replacement

#### EMC

EN 50155, EN 50121, IEC 62236-3-2 Compliant  
CE/FCC: EN 55032 (Class A), EN 55024,  
FCC Part 15 B (Class A)

#### Shock Endurance

EN 50155 EN (IEC) 61373 Category 1 Class B, Half-sine pulse, 5g, 30ms (longitudinal direction), 3g, 30ms (vertical/transverse direction) compliant

#### Vibration Endurance

3 Grms with SSD (5 to 500 Hz, X, Y, Z direction; random, operating)  
MIL-STD-810G: Method 514.6C-VL Category 4 Compliant  
EN 50155 EN (IEC) 61373 Category 1 Class B Compliant

### STORAGE

#### Hard Drive Bays

(1) Half-Sized mSATA Slot &  
(4) 15mm 2.5" Drive Bays

#### Hard Drives Supported

SATA

#### RAID

Software RAID 0, 1, 5, 10

#### Maximum Storage

Up to 16TB HDD, 2TB SSD