

BCDSF04S-RSS

BCDVideo 4-Bay Small Form Factor Rail Server









4 BAY 16 PORT POE RAIL SERVER

The BCDSF04S-RSS is powered by Intel® Core™ i5-7500T or i7-7700T processors. The integrated 8 PoE ports are M12 connectors for IP cameras. Enhanced by its robust structure and system design, the BCDSF04S-RSS is able to operate under a wide temperature range from -40°F to +158°F and vibration endurance up to 3 Grms.

This rail server is in compliance with E-Mark and EN 50155 for mobile surveillance applications. With wireless LAN modules, this user-friendly transportation embedded system can real-time transmits the video to the control center. The four swappable SATA hard drives are used for mass storage of video files.



KEY FEATURES

-  Up to 16TB Storage
-  Intel® Core™ 7th Generation Processor
-  Windows 10 Pro
-  SSD & 24/7 Duty Cycle SATA Drives
-  16GB DDR4 RAM
-  Supports Cell/GPS/Wi-Fi Modules
-  -40°C to +70°C (-40°F to +158°F)
-  EN 50155 Certified
-  3-Year Advanced Replacement Warranty

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993
 TECH SUPPORT: support@bcdinc.com

BCDSF04S-RSS R1.0 Copyright © 2021, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCDSF04S-RSS

BCDVideo 4-Bay Small Form Factor Rail Server

SYSTEM

Operating System

Windows 10 Pro

Memory

Standard Configuration: 16GB (2x 8GB)
Maximum Configuration: Up to 32GB
(2x DDR4 SO-DIMM Slots)

Processor(s)

(1) Intel® Core™ 7th Generation Processor
(Up to 4 Cores, 8 Threads, 3.80GHz)

Processor Passmark

Intel® Core™ i5-7500T: 6,950
Intel® Core™ i7-7700T: 9,288

Networking

(8) 1GbE RJ45 PoE Ports
(IEEE 802.3af/802.3at)

Expansion Slots

(2) Full-size PCIe Mini Card Slot,
(2) USB/PCIe External SIM Socket,
(2) Half-size PCIe Mini Card Slot

I/O Ports

(4) USB 3.0, (2) DB-9 or RS- 232/422/485,
(5) Antenna Openings,
(1) Terminal Block 6-in/2-out DIO

Video Outputs

(1) HDMI, (1) DVI-D, (1) VGA

Certifications

CE (Class A), FCC Class A, EN 50155,
ISO 7637-2 Compliant, IP30

Manufacturer

BCD

MECHANICAL

Form Factor

Small Form Factor

Power Supply(s)

(1) 24V 120W External (10 - 30VDC)

Operating Temperature

(Min) -40°F - (Max) 158° F [(Min) -40°C - (Max) 70° C]

Operating Humidity

0 ~ 95% (non-condensing)

Heat Dissipation

327 Max BTU/hr

Dimensions (WxDxH)

11.02" x 8.27" x 3.91" (280mm x 210.5mm x 99.2mm)

Max. Weight

12.65 lbs. (5.74 kg)

Warranty

3-Year Advanced Replacement

EMC

EN 50155, EN 50121, IEC 62236-3-2 Compliant
CE/FCC: EN 55032 (Class A), EN 55024,
FCC Part 15 B (Class A)

Shock Endurance

EN 50155 EN (IEC) 61373 Category 1 Class B, Half- sine pulse, 5g, 30ms (longitudinal direction), 3g, 30ms (vertical/transverse direction) compliant

Vibration Endurance

3 Grms with SSD (5 to 500 Hz, X, Y, Z direction; random, operating)
MIL-STD-810G: Method 514.6C-VL
Category 4 Compliant
EN 50155 EN (IEC) 61373 Category 1 Class B Compliant

STORAGE

Hard Drive Bays

(1) Half-Sized mSATA Slot &
(4) 15mm 2.5" Drive Bays

Hard Drives Supported

SATA

RAID

Software RAID 0, 1, 5, 10

Maximum Storage

Up to 16TB HDD, 2TB SSD