

BCD-HES04-I5/I7-16RJ

4-Bay Small Form Factor Harsh Environment Server

16 PORT POE HARSH ENVIRONMENT SERVER

This BCD-HES02-I5/I7-16RJ support 18-port Gigabit PoE and able to work under harsh temperatures.

Its eighteen Gigabit PoE ports allow multiple cabling to cameras and any PoE power device. Powered by an Intel® Core™ i5 or i7 processor, this unit also has SIM slots and SMA-type antenna connectors.

For storage, this high performance fanless server has four drive bays with a height of up to 15 mm and one 256G mSATA for RAID 0 and 1. The embedded device supports two 260-pin DDR4 SO-DIMM slots for up to 32GB of system memory.





KEY FEATURES



Up to 16TB Storage



Intel® Core™ 6th Generation Processor



Windows 10 Pro



Standard Temp Mixed Use SSDs



16GB DDR4 RAM



Supports Cell/GPS/Wi-Fi Modules



-25°C to +70°C (-13°F to +158°F)



(16) RJ45 PoE Ports



2-Year Standard Warranty



20 Harmonize RMM Licenses

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993 TECH SUPPORT: support@bcdinc.com



BCD-HES04-I5/I7-16RJ

4-Bay Small Form Factor Harsh Environment Server

SYSTEM

Operating System

Windows 10 Pro / Linux

Memory

Standard Configuration: 16GB (2x 8GB) Maximum Configuration: Up to 32GB, optional with ECC (2x DDR4 2133MHz SO-DIMM Slots)

Processor(s)

(1) Intel® Core™ 6th Generation Processor (Up to 4 Cores, 4 Threads, 3.4GHz)

(1) Intel® Core™ 6th Generation Processor (Up to 4 Cores, 8 Threads, 3.5GHz)

Processor Passmark

Intel® Core™ i5-6440EQ: 5,394 Intel® Core™ i7-6820EQ: 6,924

Networking

(16) 1GbE RJ45 PoE Ports (IEEE 802.3af/802.3at) (2) 1 GbE Non-PoE RJ45 ports

Expansion Slots

(4) PCle Mini Card Slot

(1) Mini PCle for PCle/USB/Internal SIM $\mbox{Card/Optional mSATA}$

(3) Mini PCle for PCle/USB/External SIM Card

I/O Ports

(4) SIM Sockets for 5G/WiFi 6/4G/3G/ LTE/GPRS/UMTS, (1) Internal, (3) External(4) USB 3.0 (External)(1) USB 2.0 (Internal)16 Isolated DIO, 4 COM RS-232/422/485

Video Outputs

(1) DVI-D & (2) DisplayPort interfaces, up to 4K resolution

Certifications

CE, FCC Class A, IP40

MECHANICAL

Form Factor

Small Form Factor

Power Supply(s)

Power Input: 6V to 78V, DC-in Power Interface: 3-pin Terminal Block: V+, V-, Frame

Ground

Ignition Control: 16-mode (Internal)
Remote Switch: 5-pin Terminal Block

Surge Protection: Up to 200V/1ms Transient Power

Operating Temperature

Operating : -25°C to 70°C (-13°F to 158°F), Fanless Storage: -40°C to 58°C (-40°F to 185°F), Fanless

Operating Humidity

95% at 70°C

Dimensions (WxDxH)

10.2" x 8.5" x 3.1" (260mm x 215mm x 79mm)

Max. Weight

9.26 lb (4.2kg)

Warranty

2-Year Standard

FMC

CE. FCC. EN50155. EN50121-3-2

Shock Endurance

IEC 60068-2-27 (with SSD, 50G, half sine, 11ms duration)

Vibration Endurance

IEC 60068-2-64 (with SSD, 5Grms STD, random 5 to 500 Hz, 3 axis)

STORAGE

Hard Drive Bays

(4) 15mm 2.5" Drive Bays (1) 256G mSATA Drive

Hard Drives Supported

SATA

RAID

JBOD

Maximum Storage

Up to 16TB

